

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEX FMG 21.0017X

Page 1 of 4

Certificate history:

Status:

Current

Issue No: 0

Date of Issue:

2022-08-16

Applicant:

Anyload Weigh & Measure Inc.

6855 Antrim Avenue

Burnaby, British Columbia V5J 4M5

Canada

Equipment:

101, 102, 106, 107, 108, 110, 112, 202, 247, 266, 276, 296, 363, 535, 563, 651 series Load Cells, J04, J06, J08, J12

series Junction Boxes

Optional accessory:

Type of Protection:

Ex la

Marking:

Installations with single load cells (no junction box)

Ex la IIC T6 Ga Ex la IIIC T83°C Da

Installations with multiple load cells (with junction box)

Ex la IIC T4 Ga

Approved for Issue on behalf of the IECEx Certification Body:

J. E. Marquedant

Position:

Signature:

(for printed version)

Date:

(for printed version)

VP, Manager - Electrical Systems

13 September 2022

1. This certificate and schedule may only be reproduced in full.

This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

FM Approvals LLC 1151 Boston-Providence Tumpike Norwood, MA 02062 United States of America



Vanitarial star EM to Least Group



Certificate No.:

IECEX FMG 21.0017X

Page 2 of 4

Date of issue:

2022-08-16

Issue No: 0

Manufacturer:

Anyload Weigh & Measure Inc.

6855 Antrim Avenue

Burnaby, British Columbia V5J 4M5

Canada

Manufacturing locations: Anyload Weigh & Measure Inc.

6855 Antrim Avenue

Burnaby, British Columbia V5J 4M5

Canada

ANYLOAD YOUNGZON TRANSDUCER (HANGZHOU) CO.

LTD

518, 18th Street Qlantang New Area

Hangzhou City, Zhejlang 310018

China

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017

Edition:7.0

Explosive atmospheres - Part 0: Equipment - General requirements

IEC 60079-11:2011

Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

Editlon:6.0

This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

US/FMG/ExTR21.0020/00

Quality Assessment Reports:

GB/FME/QAR22.0004/00

GB/FME/QAR22.0005/00



Certificate No.:

IECEX FMG 21.0017X

Page 3 of 4

Date of issue:

2022-08-16

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

101, 102, 106, 107, 108, 110, 112, 202, 247, 266, 276, 296, 363, 535, 563, 651 series, Load cells.

J04, J06, J08, J12 series, Junction boxes.

SPECIFIC CONDITIONS OF USE: YES as shown below:

1. The enclosure contains aluminum and is considered a potential risk of ignition by impact or friction. Care must be taken during installation to prevent impact or friction.

2. When two barriers are used, both barriers shall be connected to the same ground reference.



Certificate No.:

IECEx FMG 21.0017X

Page 4 of 4

Date of issue:

2022-08-16

Issue No: 0

Equipment (continued):

abcde-f-g-h-Ex. Load Cell.

Refer to the Annex for details.

abcde-f-Ex. Junction Box.

Refer to the Annex for details.

Annex:

Annex to certificate IECEx FMG 21.0017X.pdf

Annex to certificate #IECEx FMG 21.0017X

abcde-f-g-h-Ex. Load Cell. abc: Model series 101, 102, 106, 107, 108, 110, 112, 202, 247, 266, 276, 296, 363, 535, 563 or 651; d: Structural code A to Z (minor differences in enclosure shape, not affecting the interfaces); e: Enclosure material A (aluminum), H (alloy steel), S (stainless steel); f: Structural variations including seal type, threading, shape, size or dimensions, load cell sensitivity, equipped with lightning/surge protection 101: LE, GS, AK, LS, LK 102: EL, GT, 02 106: 20, 02, CP, F, FB, ES 107: 02, 20, 30 108: 3MUN, TD, UN, AD, AL, YM, 01, LL, MT, FL, ST, VS, LP 110: BL 112: blank 202: blank 247: LH, UN, WM, LL, 01, 02, 03 266: PT 276: blank 296: blank 363: AN 535: blank 563: 30, RS, SB, MT, WBL, 23, 23SE, 23LE, FK, RT, MS, LB, LF, GS, AS, BK, UN 651: 22, 55, UN, 66, BC, UN, CS, GS; g: Capacity code: 101: 1kg-20t 102: 100kg-200t 106: 100kg-600t 107: 1t-20t 108: 100g-2t 110: 1t-120t 112: 0.14Nm-11.3Nm 202: 3.75kg-275kg 247: 1kg-10t 266: 25kg-100t 276: 5t-100t 296: 5kg-10t 363: 500kg-300t 535: 2t-100t 563: 5kg-20t 651: 6kg-1t h: Other variations signifying parameters not affecting the electrical circuitry, interfaces, or the main structural design, such as cable length, cable type, connector type, labeling, etc. 101: YZ, xxm (xx can be any number) or blank

102: YZ, xxm (xx can be any number) or blank 106: YZ, xxm (xx can be any number) or blank 107: YZ, xxm (xx can be any number) or blank 108: YZ, xxm (xx can be any number) or blank 110: YZ, xxm (xx can be any number) or blank 112: xxm (xx can be any number) or blank 202: xxm (xx can be any number) or blank 247: YZ, xxm (xx can be any number) or blank 266: YZ, xxm (xx can be any number) or blank 276: xxm (xx can be any number) or blank 296: YZ, xxm (xx can be any number) or blank 363: YZ, xxm (xx can be any number) or blank 535: YZ, xxm (xx can be any number) or blank 563: YZ, xxm (xx can be any number) or blank 561: YZ, xxm (xx can be any number) or blank 651: YZ, xxm (xx can be any number) or blank

abc-def-Ex. Junction Box.

abc: Model series

J04, J06, J08 or J12;

d: Trimming code

E (excitation trimming), S (signal trimming);

e: Enclosure material

A (aluminum), S (stainless steel);

f: Variations

16 (year 2016 released version), E (expansion port), FS (smaller in size), I (no section trimming and lightning protection), II (no section trimming but with lightning protection), III (with section trimming and lightning protection)